



Safety Data Sheet

SECTION 1. IDENTIFICATION

Product name : R1233zd

Product Use Description : Refrigerant, Heat transfer fluid

Tiba International For Refrigeration

Headquarter: 54 Tayaran Street - Nasr City - Cairo - Egypt.

Tel.: (+202) 22639232 Fax: (+202) 24029417

Website: www.intertiba.com

Mobile: +20 114 7905 214 / + 20 111 0004 020

E-mail: info@intertiba.com sales@intertiba.com

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Form : Liquefied gas

Form : liquid, clear

Color : colourless

Odor : slight

Classification of the substance or mixture

Classification of the : Gases under pressure, Liquefied gas

substance or mixture Simple Asphyxiant

GHS Label elements, including precautionary statements



Symbol(s)



Signal word : Warning

Hazard statements : Contains gas under pressure; may explode if heated.

May displace oxygen and cause rapid suffocation.

Precautionary statements : **Prevention:**

Use personal protective equipment as required.

Storage:

Protect from sunlight. Store in a well-ventilated place.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Substance

Chemical name	CAS-No.	Concentration
trans-1-Chloro-3,3,3-trifluoropropene	102687-65-0	>99.00 %

SECTION 4. FIRST AID MEASURES

Inhalation : Remove to fresh air. If not breathing, give artificial respiration.

If breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is present. Call a physician.

Skin contact : After contact with skin, wash immediately with plenty of water.

If symptoms persist, call a physician. Take off all contaminated clothing immediately. Wash contaminated clothing before re-

use.



for at least 15 minutes. Call a physician if irritation develops or

persists.

Ingestion : If victim is fully conscious, give a cupful of water. Do not induce

vomiting without medical advice. Never give anything by mouth

to an unconscious person. Call a physician immediately.

Notes to physician

Indication of immediate medical attention and special treatment needed, if necessary Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : The product is not flammable.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray

Carbon dioxide (CO2)

Dry chemical

Foam

Specific hazards during firefighting

This product is not flammable at ambient temperatures and

atmospheric pressure.

However, this material can ignite when mixed with air under

pressure and exposed to strong ignition sources.

Container may rupture on heating.

Cool closed containers exposed to fire with water spray.

Do not allow run-off from fire fighting to enter drains or water

courses.

Vapours are heavier than air and can cause suffocation by

reducing oxygen available for breathing.

Exposure to decomposition products may be a hazard to

health.

Fire may cause evolution of:

Hydrogen fluoride

Gaseous hydrogen chloride (HCI).

Carbon oxides

Halogenated compounds

Carbonyl halides

Special protective equipment

for firefighters

: In the event of fire and/or explosion do not breathe fumes.

Wear self-contained breathing apparatus and protective suit.

No unprotected exposed skin areas.



SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Wear personal protective equipment. Unprotected persons

must be kept away.

Remove all sources of ignition.

Ventilate the area.

Vapours are heavier than air and can cause suffocation by

reducing oxygen available for breathing. Avoid accumulation of vapours in low areas.

Unprotected personnel should not return until air has been

tested and determined safe.

Ensure that the oxygen content is >= 19.5%.

Environmental precautions

Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers).

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Handling

Precautions for safe handling

Handle with care.

Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing.

Follow all standard safety precautions for handling and use of

compressed gas cylinders. Use authorized cylinders only.

Protect cylinders from physical damage.

Do not puncture or drop cylinders, expose them to open flame

or excessive heat.

Do not pierce or burn, even after use. Do not spray on a naked

flame or any incandescent material.

Do not remove screw cap until immediately ready for use.



Always replace cap after use.

Advice on protection against fire and explosion : Can form a combustible mixture with air at pressures above

atmospheric pressure.

Keep product and empty container away from heat and

sources of ignition.

Storage

incompatibilities

Conditions for safe storage, including any

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 55 °C.

Keep containers tightly closed in a dry, cool and well-ventilated

place.

Storage rooms must be properly ventilated.

Ensure adequate ventilation, especially in confined areas.

Protect cylinders from physical damage. Store away from incompatible substances.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures Ensure that eyewash stations and safety showers are close to

the workstation location.

Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing.

Engineering measures : Use with local exhaust ventilation.

Perform filling operations only at stations with exhaust

ventilation facilities.

Eye protection : Wear as appropriate:

Safety glasses with side-shields

Safety goggles

Hand protection Impervious gloves

Gloves must be inspected prior to use.

Replace when worn.

Skin and body protection : Wear as appropriate:

Solvent-resistant gloves

Solvent-resistant apron and boots If splashes are likely to occur, wear:

Protective suit

Respiratory protection : In case of insufficient ventilation wear suitable respiratory



equipment.

Wear a positive-pressure supplied-air respirator.

For rescue and maintenance work in storage tanks use self-

contained breathing apparatus.

Use NIOSH approved respiratory protection.

Hygiene measures

: Handle in accordance with good industrial hygiene and safety

practice.

Avoid contact with skin, eyes and clothing. Do not breathe vapours or spray mist.

Ensure adequate ventilation, especially in confined areas. Remove and wash contaminated clothing before re-use. Contaminated work clothing should not be allowed out of the

workplace.

Keep working clothes separately.

Wash hands before breaks and immediately after handling the

product.

Exposure Guidelines

Exposure Guidelli	103		
Components	CAS-No.	Value	Control parameters
trans-1-Chloro- 3,3,3- trifluoropropene	102687-65-0	TWA : Time weighted average	(800 ppm)

trans-1-Chloro- 3,3,3- trifluoropropene	102687-65-0	TWA : Time weighted average	(800 ppm)

trans-1-Chloro-	102687-65-0	TWA:	(800 ppm)
3,3,3-		Time	
trifluoropropene		weighted	
		average	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Liquefied gas liquid, clear



Color : colourless

Odor : slight

Melting point/range : < -90 °C

Method: OECD Test Guideline 102

Boiling point/boiling range : 19 °C

Method: OECD Test Guideline 103

Flash point : Method: ISO 2719

Note: Not applicable

Flammability : The product is not flammable.

Method: Flammability (gases)

Lower explosion limit : Note: None

Upper explosion limit : Note: None

Vapor pressure : 1,516 hPa

at 30 °C(86 °F)

Vapor density : Note: (Air = 1.0), not determined

Density : 1.27 g/cm3

Water solubility : 1.90 g/l at 20 °C

Method: OECD Test Guideline 105

Partition coefficient: n-

octanol/water

: log Pow: 2.2 at 25 °C

Ignition temperature : 380 °C at 986.8 - 1,035.9 hPa

Method: DIN 51794



Decomposition temperature : > 250 °C

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : 130.5 g/mol

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous : Polymerisation can occur. reactions

Conditions to avoid : Pressurized container. Protect from sunlight and do not

expose to temperatures exceeding 55 °C.

Can form a combustible mixture with air at pressures above

atmospheric pressure.

Do not mix with oxygen or air above atmospheric pressure.

Incompatible materials : Strong oxidizing agents

Finely divided magnesium Finely divided aluminium

Hazardous decomposition :

products

: Halogenated compounds

Carbon oxides Hydrogen fluoride Carbonyl halides

Gaseous hydrogen chloride (HCI).

SECTION 11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity : LC50: 120000 ppm

Exposure time: 4 h Species: Rat

Skin irritation : Species: Rabbit

Result: No skin irritation



Classification: Not classified as a skin irritant in animal testing.

Method: OECD Test Guideline 404

Exposure time: 4 h

Sensitisation : Result: Does not cause skin sensitisation.

Classification: Patch test on human volunteers did not

demonstrate sensitisation properties.

Repeated dose toxicity : Species: Rat

Application Route: Inhalation Exposure time: 4 Weeks

NOEL: 4500 ppm Note: Subacute toxicity

Genotoxicity in vitro

Test Method: Mutagenicity (Salmonella typhimurium - reverse

mutation assay)

Metabolic activation: with and without metabolic activation

Result: negative

: Test Method: Mutagenicity (Escherichia coli - reverse mutation

assay

Metabolic activation: with and without metabolic activation

Result: negative

Method: OECD Test Guideline 471

: Test Method: Chromosome aberration test in vitro

Cell type: Human lymphocytes

Result: negative

Method: OECD Test Guideline 473

Genotoxicity in vivo : Species: Rat

Cell type: Bone marrow

Method: Mutagenicity (micronucleus test)

Result: negative

Test Method:

Genotoxicity in vivo : Species: Mouse

Cell type: Bone marrow

Method: Mutagenicity (micronucleus test)

Result: negative

Reproductive toxicity : Species: Rabbit



Note: No-observed-effect level - 15,000 ppm

: Species: Rat

Note: No-observed-effect level - 10,000 ppm

Teratogenicity : Species: Rabbit

Note: No-observed-effect level - 15,000 ppm

: Species: Rat

Note: No-observed-effect level - 10,000 ppm

Further information

Note: Excessive exposure may cause central nervous system

effects including drowsiness and dizziness. Cardiac

Sensitization (dog): No effects for exposures up to 100000

ppm.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity effects

Toxicity to fish : LC50: 38 mg/l

Exposure time: 96 h

Species: Oncorhynchus mykiss (rainbow trout)

Method: OECD Test Guideline 203

Immobilization EC50: 82 mg/l Exposure time: 48 h

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 202

EC50: > 215 mg/l Exposure time: 72 h

Species: Pseudokirchneriella subcapitata (green algae)

Method: OECD Test Guideline 201

Growth rate NOEC: 115 mg/l



Exposure time: 72 h

Species: Pseudokirchneriella subcapitata (green algae)

Method: OECD Test Guideline 201

Elimination information (persistence and degradability)

Bioaccumulation : Note: Due to the distribution coefficient n-octanol/water,

accumulation in organisms is not expected.

Biodegradability : Result: Not readily biodegradable.

Value: 0 %

Method: OECD 301 D

Further information on ecology

Ecotoxicology Assessment

Results of PBT assessment

This substance is not considered to be very persistent and very bioaccumulating (vPvB)., This substance is not considered to be persistent, bioaccumulating and toxic (PBT).

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Observe all Federal, State, and Local Environmental

regulations.

Note : Where possible recycling is preferred to disposal or

incineration.

SECTION 14. TRANSPORT INFORMATION

DOT UN/ID No. : UN 3163

Proper shipping name : LIQUEFIED GAS, N.O.S.

Hazard Labels 2.2

IATA UN/ID No. : UN 3163

Description of the goods : LIQUEFIED GAS, N.O.S.

(Trans-1-Chloro-3,3,3-trifluoropropene)

Class : 2.2



Hazard Labels : 2.2 Packing instruction (cargo : 200

aircraft)

Packing instruction : 200

(passenger aircraft)

IMDG UN/ID No. : UN 3163

> Description of the goods : LIQUEFIED GAS, N.O.S.

(TRANS-1-CHLORO-3,3,3-TRIFLUOROPROPENE)

Class : 2.2 Hazard Labels : 2.2 : F-C, S-V EmS Number Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

Inventories

US. Toxic Substances On TSCA Inventory

Control Act

Australia. Industrial On the inventory, or in compliance with the inventory

Chemical (Notification and

Assessment) Act

Canada. Canadian : All components of this product are on the Canadian DSL

Environmental Protection Act (CEPA). Domestic Substances List (DSL)

Japan. Kashin-Hou Law : On the inventory, or in compliance with the inventory

List

Korea. Existing Chemicals

Inventory (KECI)

and Nuclear Waste Control Act

: trans-1-Chloro-3,3,3-102687-65-0

trifluoropropene

China. Inventory of Existing : On the inventory, or in compliance with the inventory

Chemical Substances



(IECSC)

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand : On the inventory, or in compliance with the inventory

National regulatory information

SARA 302 Components: No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 Components : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards : Acute Health Hazard

Sudden Release of Pressure Hazard

California Prop. 65 : This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

New Jersey RTK : trans-1-Chloro-3,3,3- 102687-65-

trifluoropropene

Pennsylvania RTK : trans-1-Chloro-3,3,3- 102687-65-

trifluoropropene (

Health hazard : 2 2 Flammability : 0 0

Flammability : 0
Physical Hazard : 0

Physical Hazard : 0
Instability : 0

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.