

## Safety Data Sheet

### R-124

#### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** R-124  
**OTHER NAME:** Chlorotetrafluoroethane  
**USE:** Refrigerant Gas

#### Tiba International For Refrigeration

Headquarter: 54 Tayaran Street – Nasr City – Cairo – Egypt.

Tel.: (+202) 22639232 Fax : (+202) 24029417

Website: [www.intertiba.com](http://www.intertiba.com)

Mobile: +20 114 7905 214 / + 20 111 0004 020

E-mail: [info@intertiba.com](mailto:info@intertiba.com) [sales@intertiba.com](mailto:sales@intertiba.com)

#### 2. HAZARDS IDENTIFICATION

<b>CLASSIFICATION:</b>	Gases under pressure, Liquefied Gas
<b>SIGNAL WORD:</b>	WARNING
<b>HAZARD STATEMENT:</b>	Contains gas under pressure, may explode if heated
<b>SYMBOL:</b>	Gas Cylinder
<b>PRECAUTIONARY STATEMENT:</b>	<b>STORAGE:</b> Protect from sunlight, store in a well ventilated place



**EMERGENCY OVERVIEW:** Colorless, volatile liquid with ethereal and faint sweetish odor. Non-flammable material. Overexposure may cause dizziness and loss of concentration. At higher levels, CNS depression and cardiac arrhythmia may result from exposure. Vapors displace air and can cause asphyxiation in confined spaces. At higher temperatures, (>250°C), decomposition products may include Hydrochloric Acid (HCl), Hydrofluoric Acid (HF) and carbonyl halides.

#### POTENTIAL HEALTH HAZARDS

**SKIN:** Irritation would result from a defatting action on tissue. Liquid contact could cause frostbite.

**EYES:** Liquid contact can cause severe irritation and frostbite. Mist may irritate.

**INHALATION:** R-124 is low in acute toxicity in animals even at concentrations of 5% (50,000 ppm). However, when oxygen levels in air are reduced to 12-14% by displacement, symptoms of asphyxiation, loss of coordination, increased pulse rate and deeper respiration will occur. At high levels, cardiac arrhythmia may occur.

**INGESTION:** Ingestion is unlikely because of the low boiling point of the material. Should it occur, discomfort in the gastrointestinal tract from rapid evaporation of the material and consequent evolution of gas would result. Some effects of inhalation and skin exposure would be expected.

**DELAYED EFFECTS:** None Known

Ingredients found on one of the OSHA designated carcinogen lists are listed below.

**INGREDIENT NAME**

**NTP STATUS**

**IARC STATUS**

**OSHA LIST**

No ingredients listed in this section

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

**INGREDIENT NAME**

**CAS NUMBER**

**WEIGHT %**

Chlorotetrafluoroethane

2837-89-0

100

**COMMON NAME and SYNONYMS**

R-124; HCFC124

There are no impurities or stabilizers that contribute to the classification of the material identified in Section 2

### 4. FIRST AID MEASURES

**SKIN:** Promptly flush skin with water until all chemical is removed. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. Get medical attention if symptoms persist.

**EYES:** Immediately flush eyes with large amounts of water for at least 15 minutes (in case of frostbite, water should be lukewarm, not hot) lifting eyelids occasionally to facilitate irrigation. Get medical attention if symptoms persist.

**INHALATION:** Immediately remove patient to fresh air. If breathing has stopped, give artificial respiration. Use oxygen as required, provided a qualified operator is available. Get medical attention immediately. DO NOT give epinephrine (adrenaline).

**INGESTION:** Ingestion is unlikely because of the physical properties and is not expected to be hazardous. DO NOT induce vomiting unless instructed to do so by a physician.

**ADVICE TO PHYSICIAN:** Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions.

### 5. FIRE FIGHTING MEASURES

**FLAMMABLE PROPERTIES**

**FLASH POINT:**

Gas, not applicable per DOT regulations

**FLASH POINT METHOD:**

Not applicable

**AUTOIGNITION TEMPERATURE:**

Unknown

**UPPER FLAME LIMIT (volume % in air):**

None\*

**LOWER FLAME LIMIT (volume % in air):**

None\*

\*Based on ASHRAE Standard 34 with match ignition

**FLAME PROPAGATION RATE (solids):**

Not applicable

**OSHA FLAMMABILITY CLASS:**

Not applicable

## EXTINGUISHING MEDIA:

Use any standard agent – choose the one most appropriate for type of surrounding fire (material itself is not flammable)

## UNUSUAL FIRE AND EXPLOSION HAZARDS:

R-124 is not flammable at ambient temperatures and atmospheric pressure. However, this material will become combustible when mixed with air under pressure and exposed to strong ignition sources.

Contact with certain reactive metals may result in formation of explosive or exothermic reactions under specific conditions (e.g. very high temperatures and/or appropriate pressures).

## SPECIAL FIRE FIGHTING PRECAUTIONS/INSTRUCTIONS:

Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool.

## 6. ACCIDENTAL RELEASE MEASURES

### IN CASE OF SPILL OR OTHER RELEASE:

(Always wear recommended personal protective equipment.)

Evacuate unprotected personnel. Product dissipates upon release. Protected personnel should remove ignition sources and shut off leak, if without risk, and provide ventilation. Unprotected personnel should not return to the affected area until air has been tested and determined safe, including low-lying areas.

Spills and releases may have to be reported to Federal and/or local authorities. See Section 15 regarding reporting requirements.

## 7. HANDLING AND STORAGE

### NORMAL HANDLING:

(Always wear recommended personal protective equipment.)

Avoid breathing vapors and liquid contact with eyes, skin or clothing. Do not puncture or drop cylinders, expose them to open flame or excessive heat. Use authorized cylinders only. Follow standard safety precautions for handling and use of compressed gas cylinders.

R-124 should not be mixed with air above atmospheric pressure for leak testing or any other purpose. See Section 5: Unusual Fire and Explosion Hazards

### STORAGE RECOMMENDATIONS:

Store in a cool, well-ventilated area of low fire risk and out of direct sunlight. Protect cylinder and its fittings from physical damage. Storage in subsurface locations should be avoided. Close valve tightly after use and when empty.

### INCOMPATIBILITIES:

Freshly abraded aluminum surfaces at specific temperatures and pressures may cause a strong exothermic reaction. Chemically reactive metals: potassium, calcium, powdered aluminum, magnesium, and zinc.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### ENGINEERING CONTROLS:

Provide local ventilation at filling zones and areas where leakage is probable. Mechanical (general) ventilation may be adequate for other operating and storage areas.

## PERSONAL PROTECTIVE EQUIPMENT

### **SKIN PROTECTION:**

Skin contact with refrigerant may cause frostbite. General work clothing and gloves (leather) should provide adequate protection. If prolonged contact with liquid or gas is anticipated, insulated gloves constructed of PVA, neoprene or butyl rubber should be used. Any contaminated clothing should be promptly removed and washed before reuse.

### **EYE PROTECTION:**

For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear chemical safety goggles.

### **RESPIRATORY PROTECTION:**

None generally required for adequately ventilated work situations. For accidental release or non-ventilated situations, or release into confined space, where the concentration may be above the PEL of 1,000 ppm, use a self-contained, NIOSH approved breathing apparatus or supplied air respirator. For escape: use the former or a NIOSH approved gas mask with organic vapor canister.

### **ADDITIONAL RECOMMENDATIONS:**

Where contact with liquid is likely, such as in a spill or leak, impervious boots and clothing should be worn. High dose-level warning signs are recommended for areas of principle exposure. Provide eyewash stations and quick-drench shower facilities at convenient locations. For tank cleaning operations, see OSHA regulations, 29 CFR 1910.132 and 29 CFR 1910.133.

## EXPOSURE GUIDELINES

### INGREDIENT NAME

Chlorotetrafluoroethane

### ACGIH TLV

None

### OSHA PEL

None

### OTHER LIMIT

\*1000 ppm TWA (8hr)

\* = Workplace Environmental Exposure Level (AIHA)

### **OTHER EXPOSURE LIMITS FOR POTENTIAL DECOMPOSITION PRODUCTS:**

Hydrogen Fluoride: ACGIH TLV = 2ppm ceiling, 0.5ppm TLV-TWA

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>APPEARANCE:</b>	Clear, colorless liquid and vapor
<b>PHYSICAL STATE:</b>	Gas at ambient temperatures
<b>MOLECULAR WEIGHT:</b>	136.45
<b>CHEMICAL FORMULA:</b>	CHClFCF <sub>3</sub>
<b>ODOR:</b>	Faint ethereal odor
<b>SPECIFIC GRAVITY (water = 1.0):</b>	1.34 @ 30°C (86°F)
<b>SOLUBILITY IN WATER (weight %):</b>	Unknown
<b>pH:</b>	Neutral
<b>BOILING POINT:</b>	-12°C (10.4°F)
<b>FREEZING POINT:</b>	-199°C (-326°F)
<b>VAPOR PRESSURE:</b>	49.3 psia @ 70°F 126.1 psia @ 130°F

<b>VAPOR DENSITY (air = 1.0):</b>	4.7	
<b>EVAPORATION RATE:</b>	>1	<b>COMPARED TO:</b> $CCl_4 = 1$
<b>% VOLATILES:</b>	100	
<b>ODOR THRESHHOLD:</b>	High	
<b>FLAMMABILITY:</b>	Not applicable	
<b>LEL/UEL:</b>	None/None	
<b>RELATIVE DENSITY:</b>	1.37 g/cm <sup>3</sup> at 21.1 C	
<b>PARTITION COEFF (n-octanol/water)</b>	Log Pow: 1.94. Note: This product is more soluble than octanol	
<b>AUTO IGNITION TEMP:</b>	Not Determined	
<b>DECOMPOSITION TEMPERATURE:</b>	>250 degrees C	
<b>VISCOSITY:</b>	Not applicable	
<b>FLASH POINT:</b>	Not applicable	

(Flash point method and additional flammability data are found in Section 5.)\

## 10. STABILITY AND REACTIVITY

### NORMALLY STABLE: (CONDITIONS TO AVOID):

The product is stable.

Do not mix with oxygen or air above atmospheric pressure. Any source of high temperatures, such as lighted cigarettes, flames, hot spots or welding may yield toxic and/or corrosive decomposition products.

### INCOMPATIBILITIES:

(Under specific conditions: e.g. very high temperatures and/or appropriate pressures) – Freshly abraded aluminum surfaces (may cause strong exothermic reaction). Chemically reactive metals: potassium, calcium, powdered aluminum, magnesium, and zinc.

### HAZARDOUS DECOMPOSITION PRODUCTS:

Halogens, halogen acids and possibly carbonyl halides.

### HAZARDOUS POLYMERIZATION:

Will not occur.

## 11. TOXICOLOGICAL INFORMATION

### IMMEDIATE (ACUTE) EFFECTS:

LC<sub>50</sub> : Inhalation 4 hr. (rat) -  $\geq 360,000$  ppm / Cardiac Sensitization threshold (dog) – 25,000 ppm

Central Nervous System Depression; 10 min. EC<sub>50</sub> - 140,000 ppm

### DELAYED (SUBCHRONIC AND CHRONIC) EFFECTS:

Subchronic inhalation (rat and mouse) NOEL – 15,000 ppm

Not active in a series of genetic studies.

### OTHER DATA:

Teratology – (rat and rabbit-dams); NOEL – 15,000ppm

NOEL (rat and rabbit pups); 50,000 ppm

Data indicates that material is not a teratogen at the TLV of the compound

## REPEATED DOSE TOXICITY:

Lifetime inhalation exposure of male rats was associated with a small increase in salivary gland fibrosarcomas.

## POTENTIAL HEALTH HAZARDS

**SKIN:** Irritation would result from a defatting action on tissue. Liquid contact could cause frostbite.

**EYES:** Liquid contact can cause severe irritation and frostbite. Mist may irritate.

**INHALATION:** R-124 is low in acute toxicity in animals even at concentrations of 5% (50,000 ppm). However, when oxygen levels in air are reduced to 12-14% by displacement, symptoms of asphyxiation, loss of coordination, increased pulse rate and deeper respiration will occur. At high levels, cardiac arrhythmia may occur.

**INGESTION:** Ingestion is unlikely because of the low boiling point of the material. Should it occur, discomfort in the gastrointestinal tract from rapid evaporation of the material and consequent evolution of gas would result. Some effects of inhalation and skin exposure would be expected.

**DELAYED EFFECTS:** None Known

Ingredients found on one of the OSHA designated carcinogen lists are listed below.

<u>INGREDIENT NAME</u>	<u>NTP STATUS</u>	<u>IARC STATUS</u>	<u>OSHA LIST</u>
No ingredients listed in this section			

## FURTHER INFORMATION:

Acute effects of rapid evaporation of the liquid may cause frostbite. Vapors are heavier than air and can displace oxygen causing difficulty breathing or suffocation. May cause cardiac arrhythmia.

## 12. ECOLOGICAL INFORMATION

**Degradability (BOD):** R-124 is a gas at room temperature; therefore, it is unlikely to remain in water.  
**Octanol Water Partition Coefficient:** Log  $p_{ow}$  = 1.94 indicating a low potential for bioaccumulation. (See Section 9)

## 13. DISPOSAL CONSIDERATIONS

### RCRA

<b>Is the unused product a RCRA hazardous waste if discarded?</b>	Not a hazardous waste
<b>If yes, the RCRA ID number is:</b>	Not applicable

### OTHER DISPOSAL CONSIDERATIONS:

Disposal must comply with federal, state, and local disposal or discharge laws. R-124 is subject to U.S. Environmental Protection Agency Clean Air Act Regulations Section 608 in 40 CFR Part 82 regarding refrigerant recycling.

The information offered here is for the product as shipped. Use and/or alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.



**WARNING: DO NOT vent** to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any residual must be recovered. **Contains Chlorotetrafluoroethane**, an HCFC substance which harms public health and environment by destroying ozone in the upper atmosphere. Destruction of the ozone layer can lead to increased ultraviolet radiation which, with excess exposure to sunlight, can lead to an increase in skin cancer and eye bcataracts.

**CALIFORNIA PROPOSITION 65:**

The ingredients in this product do not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**WHMIS CLASSIFICATION (CANADA):**

This product has been evaluated in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

**FOREIGN INVENTORY STATUS:**

EU - EINECS # 2206296